

GP-512

Polypropylene (Random Copolymer)



Product Description

GP-512 is a random copolymer polypropylene produced by the Unipol process. It has high melting viscosity, and is designed suitable for pipe forming. GP-512 offers excellent hydrostatic pressure resistance, impact resistance, and long-term heat resistance.

Key Features

- Hydrostatic pressure resistance
- Impact resistance
- Long-term heat stability

Applications

- Pipe (Hot & cool water supply pipe)

Typical Properties

	Item	Measuring Method		Value	Unit
Physical	Melt Flow Index (230°C, 2.16kg)	ASTM	D1238	0.25	g/10min
	Density	ASTM	D1505	0.9	g/cm ³
Mechanical	Tensile Stress (Yield)	ASTM	D638	270	kgf/cm ²
	Tensile Strain (Break)	ASTM	D638	> 500	%
	Flexural Modulus	ASTM	D790	9,000	kgf/cm ²
	Notched Izod Impact Strength (23°C)	ASTM	D256	No Break	kgf-cm/cm
	Heat Deflection Temp. (4.6kgf/cm ²)	ASTM	D648	85	°C

• NOTE : These are not to be construed as specifications

*Disclaimer : All information in this document is for reference only and is not a final product specification. The content of this document is not legally binding and suitability issues regarding final use must be determined by the user, and the user alone is responsible for the outcome. The values and information specified in this document may change without prior notice for quality enhancement of the product.