

## 1. Introduction

HANWHA P-1300 is a PVC homopolymer made by suspension polymerization. P-1300 is well known for clean surface and bright color to the finished goods due to its good gellation and low fish-eye count. It is mainly used in PVC wire extrusion and calender processing. It is recommended for high-quality product.

## 2. Applications

Automotive interior product, Compound for wire extrusion, Gasket, Leather, Hose

## 3. Properties

Properties	Methods	Unit	Typical value
Degree of polymerization	JIS K6720-2	-	1300±50
K-Value	DIN 53726	-	72
Apparent bulk density	ASTM D1895	g/cm <sup>3</sup>	0.50±0.04
Volatility	ASTM D3030	%	Below 0.30
Sieve analysis (42mesh pass)	HCC method	%	100

\*The values given above are typical test results which should be used as a guide only. They do not form the whole or part of a specification or guarantee.

## 4. Storage, Packaging, Safety

### Storage

P-1300 should be stored dry conditions and at room temperature below 25°C.

### Safety and Handling

The Hanwha Chemical Corporation provides its customers with a product specific Material Safety Data Sheet (MSDS) to cover potential health effects, safe handling, use and transportation. Hanwha Chemical Corporation strongly encourage its customers to review MSDS on its products and other materials prior to their use. P-1300 is normally supplied as a power in 25kg polypropylene inner coated paper bag, 500kg flecon bag as well as in bulk form. P-1300 is not formulated to contain any hazardous or regulated materials such as lead, cadmium, mercury, and chromium compounds. And Hanwha Chemical

Corporation guarantee that P-1300 do not include any hazardous or regulated materials during the manufacturing process.

## General Information

The data and recommendations contained in this brochure represent the current state of our knowledge and serve as a guide only to our products and their potential applications. Therefore, no warranty of specific properties of the products mentioned herein nor of their suitability or fitness for a particular purpose is implied.

Further information and recommendations for processing can be obtained from our technical support staff and representatives.